



Designed for permanent installation in the apparatus, the FirePRO Series Truck Charger provides a rugged, space-saving solution to keep your FirePRO cameras ready at all times. Available in single, double, or triple bank configurations, it gives departments the flexibility to support any truck setup. Its low-profile design ensures a clean install without sacrificing durability or reliability.

What's included in the box:

- Truck Charger Unit(s)
- Power Supply (For AC Power)
- AC plugs for US, EU, UK (For Power Supply)
- Safety Manual
- Accessory Kit:
 - Fuse holder and fuse (Auto 3 A 32 V DC Blade Mini)
 - Self tapping screws
 - Terminal connector
 - 18 AWG stranded SAE wire (6 ft)

SPECIFICATIONS	
Input Voltage	9 V to 36 V DC
Max Input Current	1.3 A
Power Rating	12 W
Operating Temp	32°F to 115°F (During Charge)
Storage Temp	-4°F to 140°F
Replaceable Fuse	3 A mini ATO/ATC fuse
Charge Time	4 hours
Dimensions (Single)	6.25 x 4 x 2 Inches
Dimensions (Double)	7.5 x 8.25 x 2.25 Inches
Dimensions (Triple)	7.5 x 12.5 x 2.25 Inches
NFPA Standard	Meets NFPA 1901 Requirements for Equipment Mounting and Containment



Single Bank Charger

Part Number: FC-AAA



Double Bank Charger

Part Number: FC-AAA2



Triple Bank Charger

Part Number: FC-AAA3

Seek more at thermal.com

6300 Hollister Ave, Santa Barbara, CA 93117

Seek Thermal engineers, designs and manufactures high quality thermal imaging products and core platforms for consumer, commercial, and heat sensing IoT data applications. With headquarters in Santa Barbara, California, the global hub of thermal imaging innovation, the company has developed breakthrough thermal imaging camera cores that will enable a range of affordable products for use at home, work and play. For more information visit thermal.com and follow #seekthermal on Instagram and @seekthermal on X.